



+65 6839 6500

floatel.commercial@paccoffshore.com.sg www.posh.com.sg

# **POSH Elegance**



## 238 PAX / 88M DIESEL ELECTRIC / OFFSHORE CONSTRUCTION VESSEL

### PRINCIPAL PARTICULARS

2016 Year Built Flag Call Sign Singapore 9V3415

Builders PAXOCEAN Engineering Zhuhai Co., Ltd.

Official No

Classification ABS + A1 (E) Offshore Support Vessel (SPS, FFVII), +ACCU, +AMS, +DPS-2, CRC, UWILD

### **DIMENSIONS**

Approx 88 m Length Overall (LOA) Approx 78.6 m Length BP Beam Moulded 20.0 m Depth Moulded 8.0 m Draft (design) 6.0 m Draft (minimum) 4.6 m

### **TONNAGE**

TBA Gross Tonnage Net Tonnage TBA DWT 6.0 m draft

### **DECK LOADING**

Abt 760 m<sup>2</sup> (main deck), 40m<sup>2</sup> (first deck) Deck Area 10.0 t/m<sup>2</sup>

Cargo Deck Design Load

4m x 4m space reserved Moonpool

Reefer Points 4 x 440V, 32Amp / 4 x 230V, 16Amp

### **SPEED**

Max. speed min. draft 12.0 kts

## **CAPACITIES**

Fuel Oil Approx 1,500 m<sup>3\</sup> Approx 1,000 m<sup>3</sup> Potable Water Drill Water/ Ballast Water Approx 2,000 m<sup>3</sup> Sewage Holding Approx 50 m<sup>3</sup>

Approx 15 m<sup>3</sup> / Approx 30 m<sup>3</sup> Dirty Oil / Bilge

### **DISCHARGE RATES**

Fresh Water Cargo pump 1 x 100 m<sup>3</sup>/hr @ 9bar Fuel Oil Transfer pump 1 x 60 m<sup>3</sup>/hr @ 9bar

### **MAIN PROPULSION & MACHINERY**

Main Propulsion 2 x Azimuth Propellers 1,850kW each, FPP driven by

electric motor with frequency converter

Generators 4 x Hyundai HiMSEN Diesel Engines driving 4 x 1880kW

alternators (690V / 3ph / 60Hz) Run on MDO

1 x 300kW emergency / harbour generator (440V / 3ph /

60Hz)

Tunnel Thrusters 2 x transverse tunnel bow thrusters each 1,100kW Air compressor 2 x Service Air Compressor Capacity 300m3/hr at 10 bar

(1320 gpm @ 145psi)

### DYNAMIC POSITIONING EQUIPMENT

Kongsberg K-POS DP-21 2 x DGPS (Veripos)

1 x RADius Relative Positioning System

1 x Cyscan Laser Reference System

#### **DECK EQUIPMENT**

Main Crane Kenz Electric Hydraulic Lattice Boom crane

100T@14m with man-riding capability, boom length 46m,

API 2-C & ABS Class

Auxilliary Crane 10T@15m radius

Heel Control 2x350m<sup>3</sup>/hr heeling pumps with heeling monitoring system 4 drums hydraulic winches each with 1200m x 44mm wire Mooring Winch

Anchors 4 x 7,000kg Flipper Delta Anchors

Capstans 2 x electro hydraulic Cap. 10T@15m/min

Helideck Compliance to CAP 437 & suitable for Sikorsky S92N

### LSA / FFA EQUIPMENT

Fi-Fi (Class II) 2 x FiFi pumps each capacity 3,700m<sup>3</sup>/hr@140m

4 x Remote Controlled FiFi monitors each capacity

1.800m3/hr

Compliance to latest amended SOLAS 1974 and SPS Code 2008

2 x SOLAS certified Life Boats c/w launching davits

2 x SOLAS ceritified 6-men Rescue Boats c/w launching davits

### **ACCOMMODATION SPACES / EQUIPMENT**

Mess room for 90 pax

2 x Recreation Rooms

TV room with 38 cinema type seats

1 x Smoking Room

3 x well equipped offices & 1 x conference room

Gymnasium equipped with 2 motorized treadmills, 1 cycling machine

2 Elliptical Cross Trainer & 1 multiple station

Laundry with 4 sets of heavy duty industrial washing machines & dryers Surau (Prayer room with ablution facility)

Hospital with 3 medical beds, movable with lockable wheels

Changing room with 240 individual lockers

Freezer 23m<sup>3</sup>

Chiller 26m3

Water maker 2 x 50 T/day

MARPOL Biological Sewage Treatment Plant of 240 men capacity

### ACCOMMODATION

Marine Officers/Crew 38 (including catering crew)

Passengers 200 Berth total 238

Passenger Cabins 8 x 1 - man, 13 x 2 - man, 51 x 4 - man

Cabin sizes in compliance to MLC 2006