

POSH ENTERPRISE

218 PAX / 88M DIESEL ELECTRIC / MPSV



PRINCIPAL PARTICULARS

Year Built	2015
Flag	Singapore
Call Sign	9V2393
Builders	PAXOCEAN Engineering Zhuhai Co., Ltd.
Official No	398972
Classification	ABS + A1 (E) Offshore Support Vessel (SPS, FFFVII), +ACCU, +AMS, +DPS-2, CRC

DIMENSIONS

Length Overall (LOA)	88 m
Length BP	78.6 m
Beam Moulded	20.0 m
Depth Moulded	8.0 m
Draft (design)	6.0 m
Draft (minimum)	4.6 m

TONNAGE

Gross Tonnage	5,552 T
Net Tonnage	1,665 T
DWT 6.0 m draft	3,200 T

DECK LOADING

Deck Area	Abt 740 m ² (main deck), 40m ² (mezzanine deck)
Cargo Deck Design Load	10.0 t/m ²
Moonpool	4m x 4m Space Reserved
Reefer Points	4 x 440V, 32Amp / 4 x 230V, 16Amp

SPEED

Max. speed min. draft	13.0 kts
-----------------------	----------

CAPACITIES

Fuel Oil	Approx 1,500 m ³
Potable Water	Approx 1,000 m ³
Drill Water/Ballast Water	Approx 2,000 m ³
Sewage Holding	Approx 50 m ³
Dirty Oil / Bilge	Approx 15 m ³ / Approx 30 m ³

DISCHARGE RATES

Fresh Water Cargo pump	1 x 100 m ³ /hr @ 9bar
Fuel Oil Transfer pump	1 x 60 m ³ /hr @ 9bar

MAIN PROPULSION & MACHINERY

Main Propulsion 2 x Azimuth Propellers 1850kW each, FPP driven by electric motor with frequency converter

Generators 2 x Hyundai HiMSEN Diesel Engines driving 2 x 1880kW alternators (690V / 3ph / 60Hz) Run on MDO
2 x Hyundai HiMSEN Diesel Engines driving 2 x 1460kW alternators (690V / 3ph / 60Hz) Run on MDO
1 x 300kW emergency / harbour generator (440V / 3ph / 60Hz)

Tunnel Thrusters 2 x transverse tunnel bow thrusters each 1000kW
Air compressor 2 x Service Air Compressor Capacity 300m³/hr at 10 bar (1320 gpm @ 145psi)

DYNAMIC POSITIONING EQUIPMENT

Kongsberg K-POS DP-21
2 x DGPS
1 x Radius Relative Positioning System
1 x Cyscan Laser Reference System
HIPAP 501
Tautwire Bandak MK 15B LTW

DECK EQUIPMENT

Main Crane Kenz Electric Hydraulic Lattice Boom/Subsea Crane with man-riding & active heave compensation capability. API 2-C and ABS Class.
120T @ 12m Deck lift
75T @ 16m offboard lift
50T @ 15m subsea lift up to 1500m water depth
Boom can be configured to 46m or 35 m

Auxilliary Crane 10T@15m radius
Heel Control 2x350m³/hr heeling pumps with heeling monitoring system
Mooring Winch 4 drums hydraulic winches each designed for 1200m x 44mm wire

Anchors Designed for 7,000kg FlipperDelta Anchors
Capstans 2 x electro hydraulic Cap. 10T @ 15m/min
Helideck Suitable for Sikorsky S92N
Gangway KENZ EHC 15-25/1800 Electro hydraulic pedestal mounted active heave compensated offshore Telescopic Gangway System
Nominal operating radius: 15m - 25m

LSA / FFA EQUIPMENT

Fi-Fi (Class II) 2 x FiFi pumps each capacity 3,700m³/hr@140m
4 x Remote Controlled FiFi monitors each capacity 1,800m³/hr
(manual ship handling or DP1 with closed Bus Bar)

Compliance to latest amended SOLAS 1974 and SPS Code 2008
2 x SOLAS certified Life Boats c/w launching davits
2 x SOLAS certified 6-men Rescue Boats c/w launching davits

ACCOMMODATION SPACES / EQUIPMENT

Mess room for 90 pax
2 x Recreation Rooms
TV room with 38 cinema type seats
1 x Smoking Room
3 x well equipped offices & 1 x conference room
Gymnasium equipped with 2 motorized treadmills, 1 cycling machine
2 Elliptical Cross Trainer & 1 multiple station
Laundry with 4 sets of heavy duty industrial washing machines & dryers
Surau (Prayer room with ablution facility and Majlis)
Hospital with 2 medical beds, movable with lockable wheels
Changing room with 240 individual lockers
Freezer 21m³
Chiller 26m³
Water maker 2 x 50 m³
MARPOL Biological Sewage Treatment Plant of 240 men capacity

ACCOMMODATION

Marine Officers/Crew	46 (including catering crew)
Passengers	172
Berth total	218
Passenger Cabins	8 x 1 - man, 13 x 2 - man, 46 x 4 - man Cabin sizes in compliance to MLC 2006