

OCV



VESSEL CAPABILITIES

SUBSEA CONSTRUCTION



FLEXIBLE AND CABLE LAY



MOORING



POSH DEEP C

Vessel Info

POSH Deep C is a high-specification Offshore Construction Vessel (OCV) designed for complex subsea construction, maintenance, and support operations. Equipped with a DP3 (Dynamic Positioning) system for exceptional stability and precision, POSH Deep C excels in handling the demanding challenges of offshore construction across diverse marine environments.

- Length 119.3m X Beam 27m
- Deck Area 1150m²
- Accommodation for 100 Persons
- 250T NOV Main Crane
- 30t Stern Crane
- Equipped DP3 for precise manoeuvrability
- Top Speed 14.5 Knots
- Versatility: Designed to support a wide range of offshore operations, including construction, maintenance, and subsea support operations.

PRINCIPAL PARTICULARS

YEAR BUILT	2004
FLAG	Tuvalu
CALL SIGN	T2VU5
BUILDERS	Factorias Vulcano, S.A. / Jinling Shipyard
OFFICIAL NO	9265342
CLASSIFICATION (DNV)	✕ 1A1 Supply vessel Tug BWM(T) Clean COMF(C-3, V-3) DK(+) DYNPOS(AUTRO) E0 HELDK Ice(C) SF TMON

DIMENSIONS & TONNAGE

LENGTH OVERALL (LOA)	119.3m
LENGTH BP	27m
DEPTH TO 1 ST DECK	11.6m
DEPTH TO 2 ND DECK	7.8m
GROSS TONNAGE	12,913T
NET TONNAGE	3,874t
DWT 6.0m DRAFT	7,900t

MAIN PROPULSION & MACHINERY

MAIN PROPULSION	2 x 8,120kW, 1 x Azimuth Propeller 1,200kW, Total Output 17,400kW
GENERATORS	2 x 2,420kW, 2 x 1,820kW 1 x 910kW emergency 2 x 4,800kW Shaft generator
BOW THRUSTERS	2 x 1,425kW
STERN THRUSTERS	2 x 1,425kW

DYNAMIC POSITIONING EQUIPMENT

DP CLASS / MODEL	SPD-21 / SDP11 3 x DGPS
POSITION REFERENCES	3 x Wind Sensors, 3 x MGC, 1 x HIPAP, 1 x LTW

LSA/FFA EQUIPMENT

RESCUE BOAT	1 x 6 POB Fast Rescue Boat
LIFEBOATS & DAVITS	4 x 50 POB Lifeboats
LIFE RAFTS	8 x 25 POB Life raft with full emergency pack

CRANE, ANCHOR AND HELIDECK INFORMATION

MAIN CRANE	1x 250T NOV Crane (up to 1,800m water depth)
AUXILIARY CRANE	1 x 30T @ 2000m max
CAPSTANS	2 x 15T @21mpm
HELIDECK	Designed for Super Puma EC225
ANCHORS	PORT12 shackles / STBD 14 shackles

ANCHOR HANDLING & WINCH OF WATERFALL TYPE

One Brattvaag towing/anchor handling winch of type BSL 500WX / 2SL500WX consisting of:

INNER DIAMETER	3,500mm
OUTER DIAMETER	5,700mm
WIDTH OF DRUM	5,800mm
CAPACITY	8,100m of 108mm dia. Wire

One anchor handling drum SWL 500 tonnes

Two declutch-able towing drums - secondary winches SWL 500T

INNER DIAMETER	1,500mm
OUTER DIAMETER	3,750mm
WIDTH OF DRUM	3,260mm
CAPACITY	3,600m of 90mm diameter wire

TUGGER WINCHES

Two tugger winches on 01 acc. deck, pull 20T each.

ANCHOR HANDLING & TOWING EQUIPMENT

Shark Jaws

Two hydraulic wire and chain stoppers, SWL 750T each

Towing pins

Two sets of hydraulic towing pins for bollard pull 330T. Operated from the bridge and locally

Stern rollers

2 stern rollers with length 5.000mm each and dia. 4.500mm. The stern rollers are designed for a downward pull of 750T.

SPEED

ECONOMICAL SPEED	10 Knots
MAXIMUM SPEED MINIMUM DRAFT	14.5 Knots

CAPACITIES

FUEL OIL	3,400m ³
POTABLE WATER	1,400m ³
DRILL WATER / BALLAST WATER	4,800m ³
CHAIN LOCKERS	1,909m ³
SEWAGE HOLDING	79m ³
DIRTY OIL / BILGE	74m ³
GREY WATER TANK	100m ³

DECK LOADING

DECK AREA	1150m ²
CARGO DECK DESIGN LOAD	15 T/m ² from frame 96 and aft
MOONPOOL	7.20m x 7.20m

Vessel has two WROV hangars, 1 STBD side and 1 PORT side.

ACCOMMODATION

MARINE OFFICERS / CREW	50 (crew & officers)
PASSENGERS	50
BERTH TOTAL	100
PASSENGER CABINS	54 Singles, 36 Doubles
SPS CODE / IP	50 / 50 persons

ACCOMMODATION SPACES / EQUIPMENT

MESS ROOM	1 room
RECREATION ROOM	2 rooms
OFFICE	6 offices
CONFERENCE ROOM	1 room
HOSPITAL	1 x 3 beds
GYM ROOM	2 x treadmills, 2 x Cross Trainer, 2 x multi-station
CHANGING ROOM	1 x 60 Lockers
LAUNDRY ROOM	4 x heavy-duty washers/dryers
FREEZER & CHILLER	2 x built-in freezer, 1 x built-in chiller
WATER MAKER	2 x 30T/day Reverse Osmosis
SEWAGE TREATMENT	108 men capacity