

VESSEL CAPABILITIES

SUBSEA CONSTRUCTION SUPPORT



HOOKUP



ACCOMMODATION



POSH ENTERPRISE

Vessel Info

The POSH Enterprise is a monohull Multipurpose Support Vessel (MPSV) designed for offshore operations, offering accommodation for up to 218 personnel with full facilities for extended projects at sea.

- Length 88m X Beam 20m
- Deck Area 780m²
- Accommodation for 218 Persons
- Kenz Electric Hydraulic Lattice Boom
- Fi-Fi Class II
- Equipped DP2 for precise manoeuvrability
- Top Speed 13 Knots
- Versatility: Designed to support a wide range of offshore operations, including construction, maintenance, and offshore accommodations

PRINCIPAL PARTICUL	IRS	
YEAR BUILT	2015	
FLAG	Singapore	
CALL SIGN	9V2393	
OFFICIAL NO	398972	
BUILDERS	PaxOcean Engineering Zhuhai Co., Ltd.	
CLASSIFICATION (ABS)	 № A1, Offshore Support Vessel (FFV 2, SPS), ©, № AMS, № ACCU, № DPS-2, BWT, CRC 	
DIMENSIONS & TONNAGE		
LENGTH OVERALL (LOA)	88m	
LENGTH BP	78.6m	
BEAM MOULDED	20m	
DEPTH MOULDED	8m	
DRAFT (DESIGN)	6m	
DRAFT (MINIMUM)	4.6m	
GROSS TONNAGE	5,550T	
NET TONNAGE	1,665T	
DWT 6.0m DRAFT	3,522T	
MAIN PROPULSION & MACHINERY		
MAIN PROPULSION	2 x Azimuth Propellers, 1,850kW each	
GENERATORS	2 x 1,880kW, 2 x 1,460kW , 1 x 300kW Emergency	
BOW THRUSTERS	2 x Transverse tunnel bow thrusters each 1,000kW	
DYNAMIC POSITIONING EQUIPMENT		
DP CLASS / MODEL	DP2 / KPOS DP - 21	
POSITION REFERENCES	2 x DGPS Veripos 1 x CyScan, 1 x RADius	
DISCHARGING RATES		
FUEL PUMP	1 x 60 m ³ /h @ 90 m head	
FRESH WATER PUMP	1 x 100 m ³ /h @ 90 m head	
DW/BW WATER PUMP	1 x 100 m ³ /h @ 85 m head	

	Main Hoist 120T @ 12m Aux Hoist 15T, with Man Riding Operating WD app.1500m (Single Fall)
AUXILIARY CRANE	1 x 10T @15m
SPREAD MOORING WINCH (C/W LENGTH /TENSION METERS)	4 Sets, 1,200m x 42mm each Drum Pull (1st Layer): - 40MT @ 10 m/min - 10MT @ 30 m/min Brake Holding (1st Layer): 80T
CAPSTANS	2 x 10T @ 15m/min,
HELIDECK	Cap 437 / Suitable for Sikorsky S-92
ANCHORS	7T Delta Flipper
DECK INFORMATION	
DECK AREA	740m² (Main Deck) 40m² (Mezzanine Deck)
CARGO DECK DESIGN LOAD	10T/m ²
MOONPOOL	4m x 4m Reserved Space
REEFER POINTS	4 x 440V, 32Amp (3 phase) 4 x 230V, 16Amp (3 phase)
LSA/FFA EQUIPMENT	
FI-FI (CLASS 2)	2 x FiFi pump capacity is 3,700m ³ /h @ 140m, 4 Remote operated Monitor , capacity 1800m ³ /h
RESCUE BOAT & DAVITS	2 x 6 POB, SOLAS Certified
LIFEBOATS & DAVITS	2 x 120 POB, SOLAS Certified
LIFE RAFTS	8 x 32 POB, Davit Launch
CAPACITIES	
FUEL OIL	1,500m ³
POTABLE WATER	1,000m ³
DRILL WATER / BALLAST WATER	2,000m ³
SEWAGE HOLDING	57.5m ³
DIRTY OIL / BILGE	21.8m ³ /32.6m ³
FOAM	15m ³
ANTI-HEEL	200m ³
m vessel particulars are accurate	

(Elect-hydraulic lattice boom - AHC)

MAX SPEED (MIN DRAFT)

CRANE & DECK EQUIPMENT

MAIN CRANE

6-POSH

ACCOMMODATION			
BERTH TOTAL	218		
MARINE & CATERING CREW	46		
PASSENGERS	172		
CABIN CONFIGURATIONS	9 Single, 11 Doubles, 1 Triples, 46 Quadruples		
CABIN SIZES IN COMPLIANCE WITH MLC 2006			
ACCOMMODATION SPACE	S / EQUIPMENT		
PAX & CREW MESS	90 Seats & 16 Seats		
TV ROOM	20 Seats		
RECREATION ROOMS	12 Seats & 6 Seats		
PRAYER ROOM	1 x 10 Persons		
DARK ROOM	1 @ Main deck		
HOSPITAL	1 x 2 Beds		
OFFICE	6 Offices		
CONFERENCE ROOM	1 x 12 Seats		
GYM ROOM	Multi Gym, Treadmills, Cross Trainers, Dumbbells, Exercise Bikes.		
CHANGING ROOM	1 x 240 Lockers		
LAUNDRY ROOM	4 x 20Kg Dryer, 4 x 20Kg Washer		
WATER MAKER	2 x 50 m³/day		
SEWAGE TREATMENT UNIT	1 x 240 Persons		
SPEED			
ECONOMICAL SPEED	8 Knots		

1 x 5m³/h @ 45 m head Vessels can be modified to meet specific charter requirements, POSH encourages clients to contact the POSH to confirm

DIRTY OIL/SLUDGE PUMP

13 Knots