

**VESSEL CAPABILITIES** 

**OFFSHORE TOWAGE** 



**SUPPLY LOGISTICS** 





## POSH IMPALA

## **Vessel Information**

POSH Impala is a 5,150 BHP Anchor-Handling Towing and Supply (AHTS) vessel with a 60-tonne bollard pull. Designed specifically for operations in shallow waters, POSH Impala excels in supporting offshore oil and gas projects, anchor handling for rigs and barges, towing operations, and providing supply and logistical support in coastal and nearshore environments.

- Length 64m X Beam 18.5m
- Deck Area 400m<sup>2</sup>
- 60 TBP

- Fi-Fi Class 1
- Accommodation up to 25 Persons
- Designed to support various offshore operations, such as towing, positioning and anchor handling.

PRINCIPAL PARTICULARS	
YEAR BUILT	2017
FLAG	Singapore
CALL SIGN	9V5367
BUILDERS	Paxocean Engineering Zhuhai Co Ltd
OFFICIAL NO	9830367
CLASSIFICATION (ABS)	承A1 Offshore Support Vessel (AH-TOW, Supply-HNLS, OSR-C2, FFV1), ⑤, 承 AMS, 承 ACCU, SPS, MLC-ACCOM, ENVIRO, UWILD, RW
DIMENSIONS & TONNAGE	
LENGTH OVERALL (LOA)	64m
BEAM OVERALL (BOA)	18.5m
DEPTH MOULDED	5.6m
DRAFT (DESIGN)	3.2m
DRAFT (MAXIMUM)	4.6m
DISPLACEMENT	4,208T
GROSS TONNAGE	2,252T
NET TONNAGE	675T
DWT 6.6m DRAFT	2,458T
MAIN PROPULSION & MAC	HINERY
BOW THRUSTERS	2 x 550kW transverse tunnel type
MAIN ENGINE	2 x Caterpillar 3516C1, 1920kWeach (Total 5,150 BHP)
SHAFT GENERATORS	2 x 1,500kW
DIESEL GENERATORS	2 x Caterpillar C18, 350kW each, 1 x Caterpillar C4.4
EMERGENCY GENERATORS	94kW
PROPELLERS	2 x CP Propellers in fixed nozzles
RUDDERS	Jiangsu China Empire Offshore Engineering Equipment Manufacture (4.2m)
ACCOMMODATION	
BERTH TOTAL	25
CABIN CONFIGURATIONS	7 Singles, 7 Doubles,

CRANE & DECK EQUIPMENT	
FIXED CRANE	1 x electro-hydraulic knuckle crane SWL 3.0T@16m radius
DECK CARGO AREA	400m²
DECK CARGO DIMENSION	27.6m x 14m
DECK CARGO CAPACITY	800T
DECK STRENGTH	5T/m <sup>2</sup>
REEFER POINTS	2x50Amp,440/3/6, 2x50Amp,220/3/60
CAPACITIES	
FUEL OIL	428m³
POTABLE WATER	325m <sup>3</sup>
DRILL WATER / BALLAST WATER	986m³
MUD/BRINE TANK	250.6m <sup>3</sup>
DRY BULK	113m³ (4 tanks)
DISCHARGING RATES	
FRESH WATER/PUMP	1 x 100m³/hr @ 10bar
DRILL WATER/PUMP	1 x 100m³/hr @ 10bar
FUEL/PUMP	1 x 100m³/hr @ 10bar
BRINE/PUMP	1 x 70m³/hr @ 7bar
LIQUID MUD/PUMP	1 x 70m³/hr @ 7bar
DRY BULK TANK	2 x 50m³/hr @ 5.6bar
TOW/ANCHOR HANDLING W	IRES
MAIN TOW WIRE	600m x 56mm Ø
SPARE TOW WIRE	600m x 56mm Ø
ANCHOR HANDLING WIRE	100m x 56mm Ø
ARCHOR HARDLING WIRE	100III X 30IIIIII D
MOORING EQUIPMENT	
ANCHOR	1 X HY-14SB HHP ANCHOR ANCHOR TOTAL WEIGHT: 1965Kg WEIGHT OF ANCHOR HEAD: 1265Kg
ANCHOR CHAIN	2 x 12 shackles 38mm Ø Grade 3 stud links chains
ANCHOR WINDLASS	9T @ 9m/min



ANCHOR HANDLING / TOW EQUIPMENT		
TOW/ANCHOR HANDLING	1x Hydraulic Waterfall Type	
WINCH	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
STALL PULL CAPACITY	150T	
BRAKE HOLDING CAPACITY	200T	
TOW DRUM CAPACITY	600m x 56mm Ø	
ANCHOR HANDLING CAPACITY	100m x 56mm Ø	
STORAGE REEL CAPACITY	600m x 56mm Ø	
TUGGER WINCH	2 x 10T each	
CAPSTAN	2 x 5T each	
SHARK JAWS	1 x SWL 200T	
TOW PINS	1 x SWL 200T	
STERN ROLLER	6.2m x 1.5m Ø (SWL 200T)	

LSA/FFA EQUIPMENT	
FIREFIGHTING SYSTEM	FiFi 1
FIFI PUMP	2 x 1,780m³/hr
FIFI MONITORS	2 x 1,200m³/hr (water) / 2 x 300m³/hr (foam)
SPRAY BOOMS	2 x 12m each side
DISPERSANT CAPACITY	17.7m³
FOAM CAPACITY	21.3m
RESCUE BOAT & DAVITS	1 x 9 POB
LIFE RAFTS	4 x 25 POB Life raft
LIFE BUOYS	10

## SPEED

**ECONOMICAL SPEED** 10 Knots MAXIMUM SPEED MINIMUM DRAFT 12 Knots





