

POSH MAI

Vessel Information

POSH Mai is a 49.4m Utility Maintenance Vessel (UMV) powered by 3,150 BHP. Designed for versatility and efficiency, the vessel supports a wide range of offshore operations including maintenance, repairs, and logistics support in shallow and nearshore environments.

• Length 50m X Beam 15m

Top Speed 10-12 Knots

- Deck Area 200m²
- Accommodation for 47 Persons

Built to perform a broad range of offshore maintenance and support tasks.

PRINCIPAL PARTICULARS		CRANE & DECK EQUIPME
YEAR BUILT	2016	FIXED CRANE
FLAG	Singapore	
CALL SIGN	9V5132	DECK CARGO AREA
BUILDERS	PaxOcean Engineering Pte Ltd,	DECK CARGO DIMENSION
	Zhuihai, China	DECK CARGO CAPACITY
OFFICIAL NO	9812872	DECK STRENGTH
CLASSIFICATION (ABS)	Φ A1, Offshore Support Vessel, Φ AMS, HDC (3T/M2 Main Deck), UWILD, CRC, SPS, RW	REEFER POINTS
DIMENSIONS & TONNAGE		
LENGTH OVERALL (LOA)	50m	
BEAM OVERALL (BOA)	15m	
DEPTH MOULDED	5m	
DRAFT (DESIGN)	2.90m	MOORING EQUIPMENT
DRAFT (MAXIMUM)	3.50m	ANCHOR
DISPLACEMENT	1,666T	
GROSS TONNAGE	1,285T	
NET TONNAGE	385T	ANCHOR WINDLASS
DWT 3.5m DRAFT	710T	
MAIN PROPULSION & MACH	TNERV	CAPSTAN
BOW THRUSTERS	2 x 280kW Kawasaki KT-32B3	
DOW THROSTERS	Controllable Pitch	
MAIN ENGINES	970kW@1,200rpm (2 x 1,300bhp) Caterpillar 3512C developing	
DIESEL GENERATORS	3 x 480kW Cummins KTA19-D(M1)	DISCHARGING RATES
EMERGENCY GENERATORS	1 x 91kW Cummins6BT5.9-D(M)9	FRESH WATER/PUMP
SHAFT GENERATORS		FUEL/PUMP
PROPELLERS	2 x Schottel SRP1012FP Azimuth Propellers	

ENT			DOCI
	1 x HeelaHMR240/30-2S SWL20T@4m; SWL1.5T@30m		-POSH
	200m ²		
	11m x 13m		
	400T		
	3T/m ²		
	4 X 480V, 32A - 3 PHASE 6 X 430V, 32A - 3 PHASE 6 X 230V, 16A - 2 PHASE 4 X 110V, 16A - 2 PHASE		
		CAPACITIES	
	2 x HY-14 SB HHP ANCHOR,	FUEL OIL	240 m ³
	ANCHOR TOTAL WEIGHT: 2 x 1,120Kg / Jiangsu Xiangsheng Heavy Industries Co.	POTABLE WATER	140 m ³
	YMA 30-3-45 / ZH120 / 1 X 42.8KN @ more than 10m per min		
	2 x Electro-hydraulic winches x		
_	5.0T	LSA/FFA EQUIPMENT	
		RESCUE BOAT & DAVITS	1 x 6 POB SK45KFRP Rescue Boat
		LIFE RAFTS	6 x 30 POB Life raft,
		LIFE BUOYS	8
	1 x 90m³/hr @ 2.0bar	LIFE JACKETS	56
	1 x 90m ³ /hr @ 2.0bar		

ACCOMMODATION	
BERTH TOTAL	47
CABIN CONFIGURATIONS	7 Singles, 11 Doubles, 6 Sextuple

SPEED	
ECONOMICAL SPEED	8-10 Knots
MAXIMUM SPEED MINIMUM DRAFT	12 Knots

*Vessels can be modified to meet specific charter requirements, POSH encourages clients to contact POSH to confirm vessel particulars are accurate.