



VESSEL CAPABILITIES

SUPPLY



ACCOMMODATION

__



POSH SKIMMER

Vessel Information

POSH Skimmer is a 79-meter-long multi-purpose support vessel (MPSV) with a DP2 system, with a flexible crane option, a 760m² deck area, accommodation for 79 personnel, great for offshore construction, maintenance, and subsea operations.

- Length 78.25m X Beam 21m
- Deck Area 760m²

- Equipped DP2 Class
- Accommodation up to 79 Persons
- Versatility: Designed to support a wide range of offshore operations, including construction, maintenance and subsea operations

PRINCIPAL PARTICULARS		CAPACITIES		
YEAR BUILT	2018	FUEL OIL	1,200m ³	
FLAG	Singapore	POTABLE WATER	635m ³	
CALL SIGN	9V3718	DRILL WATER / BALLAST	1,800m³	DISCHARGING RATES
BUILDERS	PaxOcean Engineering Zhuhai	DIRTY OIL / BILGE	6.2m ³ /14.3m ³	FUEL PUMP
OFFICIAL NO	Co., Ltd.	LIQUID MUD / BRINE	800m ³	FRESH WATER PUMP
OFFICIAL NO CLASSIFICATION (ABS)	# A1,®, Offshore Support Vessel (Supply-HNLS, OSR-C1), SPS, ₩ AMS, ₩ ACCU, ₩ DPS-2, MLC- ACCOM, RW, ENVIRO, UWILD, GP	DRY BULK		DW/BW WATER PUMP
		SLUDGE	200m³ (4 tanks)	LIQUID MUD PUMP
			6.2m³	
		BLACK WATER	28.4m³	BRINE PUMP
DIMENSIONS & TONNAGE	70.25	GREY WATER	28,4m³	DRY BULK PUMP AIR COMPRESSOR
LENGTH OVERALL (LOA)	78.25m	FOAM	18.8m³	DIRTY OIL/SLUDGE PUMP
LENGTH BP	71.3m	DISPERSANT	18.8m³	
BEAM MOULDED	21m	LSA/FFA EQUIPMENT		ACCOMMODATION
DEPTH MOULDED	6.8m	FI-FI (CLASS 1)	FiFi pumps, 2 x 1830 m ³ /h @120m.	BERTH TOTAL
DRAFT (DESIGN)	5.2m	FI-FI (CLASS I)	FiFi Monitors: 2 x 1200 m ³ /h	MARINE & CATERING CREW
DRAFT (MAXIMUM)	5.7m	RESCUE BOAT	1 x 10 POB Fast Rescue Boat	PASSENGERS
GROSS TONNAGE	4,055T	LIFEBOATS & DAVITS	2 x 50 POB Lifeboats, SOLAS Certified	CABIN CONFIGURATIONS
NET TONNAGE	1,216T	LIFE RAFTS	4 x 16 POB Life raft	CABIN SIZES IN COMPLIANCE
DWT 5.7m DRAFT	3,035T		SOLAS Certified	
MAIN PROPULSION & MACHINERY		ACCOMMODATION SPACES		DECK LOADING
MAIN PROPULSION	2 x Azimuth Propellers,	PAX & CREW MESS	24 Seats & 18 Seats	DECK AREA
	1,900kW each, elect-driven	TV ROOM	12 Seats	CARGO DECK DESIGN LOAD
GENERATORS	2 x 1,7000kW, 2 x 910kW , 1 x 238kW emergency	RECREATION ROOMS	1 room	DECK CARGO DIMENSION
BOW THRUSTERS	2 x transverse tunnel bow thrusters each 1,100kW	QUARANTINE STORE	1 room	DECK CARGO CAPACITY
		HOSPITAL	1 x 3 Beds	REEFER POINTS
AIR COMPRESSORS	2 x 25m ³ /min rotary screw type compressor c/w air-dryer	OFFICE	2 Offices	
	, ,	CONFERENCE ROOM	1 x 8 Seats	
DYNAMIC POSITIONING EQUIPMENT			Multi Gym, Treadmills, Cross	CRANE & DECK EQUIPMEN
DP CLASS / MODEL	2 x KONGSBERG K-POS DP-21	GYM ROOM	Trainers, Dumbbells, Exercise Bikes.	MAIN CRANE
POSITION REFERENCES	2 x DGPS Veripos 1 x CyScan, 1 x RADius	CHANGING ROOM	1 x 80 Lockers	AUXILIARY CRANE
	.,,	LAUNDRY ROOM	4 x 6Kg Dryer, 4 x 6Kg Washer	CAPSTANS
SPEED		WATER MAKER	1 x 40 m ³ /day	HELIDECK
ECONOMICAL SPEED	8 Knots	WATER MARK	. ,	ANCHORC
MAX SPEED (MIN DRAFT)	12.75 Knots	SEWAGE TREATMENT UNIT	1 x 3.15 m³/day ANCHORS 1 x 49 m³/day	ANCHURS
Vessels may be subject to modification to mee	et specific charter requirements. POSH advises clients to consult	with our team to confirm the latest vessel details and co	nfigurations	V1/25 in LinkedIn marketing



DISCHARGING RATES	
FUEL PUMP	1 x 150m³/h @ 80m head
FRESH WATER PUMP	1 x 100m³/h @ 80m head
DW/BW WATER PUMP	1 x 150m³/h @ 80m head
LIQUID MUD PUMP	1 x 100m³/h @ 20Bar
BRINE PUMP	2 x 100m³/h @ 20Bar
DRY BULK PUMP AIR COMPRESSOR	Bar 2 x 25m³/hr @ 6.5Bar
DIRTY OIL/SLUDGE PUMP	1 x 8 m³/h @ 4.5Bar
ACCOMMODATION	

79

29 50

CONFIGURATIONS 12 Singles, 22 Doubles, 1 Triples, 5 Quadruples

SIZES IN COMPLIANCE WITH MLC 2006

DECK LOADING	
DECK AREA	760m² (Main Deck)
CARGO DECK DESIGN LOAD	5T/m ²
DECK CARGO DIMENSION	47.5m X 16m
DECK CARGO CAPACITY	1,000T
REEFER POINTS	4x 440V, 62Amp (3 phase) 3x 440V, 16Amp (3 phase) 4x 230V, 32Amp (3 phase) 3x 230V, 16Amp (3 phase)

CRANE & DECK EQUIPMENT	
MAIN CRANE	*Can be fitted
AUXILIARY CRANE	1 x 4T @ 3.3m - 16m max
CAPSTANS	2 x 10 T @ 15mpm,
HELIDECK	Suitable for Super Puma AS332L2
ANCHORS	2 x AC-14 Type Anchor; 2,475 kg







each

