

HOOKUP



ACCOMMODATION





POSH XANADU

Vessel Information

POSH Xanadu is a DP3 semi-submersible utility and maintenance unit with a capacity for up to 750 personnel on board (POB). It provides a stable, high-capacity offshore working platform, supporting maintenance, hookup, and safety standby operations in challenging offshore environments.

- Length 122.4m X Beam 55m
- Deck Area 1800m²
- Accommodation up to 750 Persons

- Fi-Fi Class II
- DP3 Class
- 1 x 150T Liebherr Crane
- 1 x 100T Liebherr Crane
- Versatility: Designed to support a wide range of offshore operations, including subsea construction support, maintenance, hook-up support and accommodation.

PRINCIPAL PARTICULARS		CRANE & DECK EQUIPMENT	
YEAR BUILT	2014	STARBOARD CRANE	1 x
FLAG	Bahamas		wit
CALL SIGN	C6BJ6	PORT CRANE	1 x wit
OFFICIAL NO	9640009	WORKSHOP	106
BUILDERS	PaxOcean Engineering Zhoushan Co. Ltd, China	CLIENT WAREHOUSE	190
CLASSIFICATION (ABS)	A1, Accommodation Service,	HELIDECK D-VALIE	22.
CLASSIFICATION (ADS)	Column Stabilized Unit, Fire Fighting Vessel Class 2, AMS,	HELIDECK MAX TAKE OFF MASS (MTOM)	12.
ACCU, DPS-3, ENVIRO-OS, HAB(ACCOM), HDC (5T/m²), HELIDK, HLC1.5T/m³), PMP,	HAB(ACCOM), HDC (5T/m²), HELIDK, HLC1.5T/m³), PMP,	HELIDECK	Des eith
	RRDA, SUSTAIN-1, UWILD	ANCHORE	2

CRAILE & BECK EQUI FIELD	
1 x Liebherr BOS 4200 SWL 100T with 55m boom	
1 x Liebherr BOS 7500 SWL 150T with 60m boom	
106m²	
190m²	
22.2m	
12.6T	
Designed for helicopter operations of either Sikorsky S61N or S92	
2 x Harbour mooring anchors	

G-PQ5H

CAPACITIES	
FUEL OIL	3,215m ³
POTABLE WATER	2,168m³
FRESH WATER GENERATION CAPACITY	2 x 150T/Day RO Plant 1 x 40T/Day RO Plant

DIMENSIONS & TONNAGE	
LENGTH OVERALL - PONTOON	122.40m
LENGTH INCLUSIVE OF HELIDECK	142.75m
MAIN DECK BREADTH	55m
BEAM MOULDED	45m
DEPTH MOULDED (TOP OF LOWER PONTOON)	7.6m
DEPTH MOULDED (BOTTOM DECK BOX)	24.45m
UPPER DECK HEIGHT (ABOVE BASELINE)	30.45m
DRAFT (TRANSIT) (EXCLUDING THRUSTERS)	5.50m
DRAFT (OPERATION) (EXCLUDING THRUSTERS)	15m
DRAFT (TRANSIT) (INCLUDING THRUSTERS)	8.93m
DRAFT (OPERATION) (INCLUDING THRUSTERS)	18.43m
(INCLUDING THRUSTERS) DRAFT (OPERATION)	0.55

DECK INFORMATION	
DECK AREA	1,800m²
MAX DECK LOAD (TRANSIT)	1,800T
MAX DECK LOAD (OPERATION)	1150T
CARGO DECK DESIGN LOAD	5T/m ²
MOONPOOL	9m x 9m

2 x 2,400kW

MAIN PROPULSION & MACHINERY

GENERATORS

(BRUNVOLL)

EMERGENCY POWER

THRUSTERS (BRUNVOLL)

BOW TUNNEL THRUSTERS

ACCOMMODATION	
BERTH TOTAL	750
CABIN CONFIGURATIONS	44 Single, 339 Doubles, 7 Quadruples
SERVICE SPACES	Offices, Multi-purpose Room, Helicopter Reception Area, Stores, etc
RECREATIONAL FACILITIES	Gym, Sports Room, Internet/Game Room, Library, Cinema and Lounges
OTHER AMENITIES	Male/Female changing rooms Client office: 62pax Client conference room: 21pax
Complies with Comfort Class	

IINERY	L
8 x 3,840kW Wartsila 8L32, 690V, 60Hz	F
1 x 1,400kW Emergency Generator, 2 x UPS systems as power back-up for PA, Obstruction lights, safety systems and electronic data processing systems	R
2 x 2,038kW ASD Thrusters 5 x 2,400kW Retractable Thrusters	

Each cabin fully outfitted with en-suite bathrooms, TV, LA phone connections	AN and
priorie comineccione	

DYNAMIC POSITIONING EQ	UIPMENT
DP CLASS / MODEL	Kongsberg K-POS DP3
POSITION REFERENCES	2x DGPS, 2x RADius Interrogators, 2x sets of gangway sensors, 1x Cyscan

LSA/FFA EQUIPMENT	
FI-FI (CLASS 2)	2 x Remote operated Monitor, Capacity 3,600m ³ /h
RESCUE BOAT & DAVITS	1 x 15 POB water jet propulsion MOB Boat (max30kt) with electrohydraulic davit
LIFEBOATS & DAVITS	8 x 150 POB Noreq lifeboats with gravity davits
LIFE RAFTS	24 x 35 POB Viking life rafts with gravity davits



