



PW TENTERAM

Vessel Information

PW Tenteram is a 3,600 BHP ASD Harbour Tug that delivers 45 tonnes bollard pull (TBP) and is purpose-built for safe and efficient harbour towage operations. Equipped with Azimuth Stern Drive (ASD) propulsion, it excels at ship berthing, and manoeuvring large vessels within confined port waters.

- Length 25.8m X Beam 9.5m
- Accommodation up to 9 Persons
- 45 TBP

Designed for reliable harbour towage, vessel berthing, and manoeuvring in confined port waters.

PRINCIPAL PARTICULARS	
YEAR BUILT	2016
FLAG	Singapore
CALL SIGN	9V3334
BUILDERS	POET, China
OFFICIAL NO	400032
CLASSIFICATION (ABS)	№A1, Towing Vessel (Fire Fighting Capability), Harbor Service, ©, ♣AMS

CRANE & DECK EQUIPMENT	
FORWARD TOWING WINCH	10T @ 10m/min (1st layer)
BREAK HOLDING CAPACITY	70T @ 1^{st} layer of rope of the drum
TOW DRUM CAPACITY	1 x 200m x 12" Circumference Working towing rope
TOWING HOOK	1 x 50T with pneumatic control
DECK CRANE	1 x 1T SWL 5m max outreach



DIMENSIONS & TONNAGE	
LENGTH OVERALL (LOA)	25.8m
BEAM OVERALL (BOA)	9.50m
DEPTH MOULDED	5.0m
DRAFT (OPERATIONS)	4m
DISPLACEMENT	516.52T @ 4m
GROSS TONNAGE	294T
NET TONNAGE	88T
DWT 4.0m DRAFT	137T @ 4m

CAPACITIES	
FUEL OIL	86m ³
POTABLE WATER	49m³
FOAM TANK	3.6m ³
DISPERSANT TANK	3.6m ³

LSA/FFA EQUIPMENT

OILY WATER SEPERATOR

DISPERSANT SYSTEM

FIRE PUMP

FIRE MONITORS

3.6m ³	
	NAVTE
	EPIRB
	GPS CO
	BNWAS
	AUTO F
1 x 1,500m³/hr @ 120m head	MAGNE
1 x 1200m³/hr with remote control	SART
0.5m ³ /hr	
1 x dispersant pump c/w	

NAVIGATION & COMMUNICATION EQUIPMENT (A1+A2+A3)	
RADAR	1 x Furuno FAR 2117-D
GPS NAVIGATOR	1 x Furuno GP-170
INMARSAT C	1 x Furuno Felcom 18
WIND ANEMOMETER	1 x RM Young 05103-58
AIS	1 x Furuno FA-150
DOPLER SPEED LOG	1 x Furuno DS 80
ECHO SOUNDER	1 x Furuno FE 800
VHF RADIO TELEPHONE	2 x Furuno FM-8900S
NAVTEX RECEIVER	1 x JMC NT-1800
EPIRB	1 x McMurdo E5
GPS COMPASS	1 x Simrad MX575 Series
BNWAS	1 x Leguardian2025
AUTO PILOT	1 x Simrad AP70
MAGNETIC COMPASS	1 x Felcom-19
SART	1 x McMurdo S4

MAIN PROPULSION & MACHINERY		
MAIN ENGINES	2 x NIIGATA 6L25HX	
TOTAL BHP	2 x 1,323kW @ 750 RPM	
PROPULSION	2 x Z-Peller-ZP21, In 360 degrees steerable kort nozzles	
GENERATORS	2 x Volvo Penta D5A-BTA	
ALTERNATORS	Stamford 86kw -415V 3phase 50Hz	
HARBOUR GENERATOR	Perkin 1103A-33T G2-40kw	

BOLLARD PULL & SPEED	
BOLLARD PULL	45T
MAXIMUM SPEED MINIMUM DRAFT	11 Knots

2 veejet nozzle

ACCOMMODATION	
BERTH TOTAL	9
CABIN CONFIGURATIONS	2 Doubles, 1 Quintuple

